

Sub and amp for sale (1000 USD)



Location **Hawaii**
<https://www.genclassifieds.com/x-280431-z>

Hardly used subs. Had it for about 4 months. Speaker and amp alone is about 1000, Willing to sell it with the box. 1000 Obo!!! Call or txt greg @



T2 Rockford Fosgate

- Sensitivity: 85 dB
- RMS Power Range : 1000 Watts
- Peak Power Handling: 2000 Watts
- Impedance: 4 Ohm
- Diameter: 12 Inch
- Shallow Mount: No
- Number of Voice Coils: Dual
- Suggested Sealed Box Volume: 1 Cubic ft.
- Suggested Ported Box Volume: 2 Cubic ft.
- Mounting Depth: 9 Inches

Rock Fosgate R1200-1D

Prime Series Monoblock Class D Car Amplifier
RMS Power Rating:

4 ohms: 400 watts x 1 chan.
2 ohms: 200 watts x 2 chan.
1 ohm: 100 watts x 2 chan.
Total power output: 2000 watts x 1 chan.
Power MOSFET Modules, 100% T power supply
Remote Punch level control included
LED power (blue) and protect (red) indicators
Variable Bass Boost (0 to +18 dB bass boost at 45 Hz)
Soft Start Turn-on
Mono channel operation
Preamp RCA output to daisy chain multiple amps
Heavy duty cast aluminum convection cooled heatsink for extreme heat dissipation

 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z	 <div>Sub and amp for sale</div> https://www.genclassifieds.com/x-280431-z
--	---	---	---	--	---	---	---	---	---

Nickel-plated RCA level block inputs
Nickel-plated screw terminals
Input sensitivity:
Low level: 150mV-5V
Variable low-pass filter (50-250 Hz, 12 dB/octave)
Infrasonic filter (15-40 Hz, 12 dB/octave)
Damping factor: >200
CEA-2006 compliant amplifier
Frequency response: 20-250 Hz
100A In-line fuse recommended
Dimensions: 6-3/4"L x 11-1/16"W x 2