GenClassifieds.com

MPOWERD



Location **Vermont** https://www.genclassifieds.com/x-561675-z

Welcome to AllSun Solar Products.

Our Luci Solar Lanterns are inflatable and have a one year warranty!

Please visit our website at www.allsunsolarproducts.com

MPOWERD - Luci® Outdoor - Inflatable Solar Lantern (12-Pack)


* Free Shipping * One Year Warranty * 2015 Summer Sale *

During checkout, the quantity of one equals (12) solar lanterns.

The outdoor enthusiast's new best friend. With Luci's hardy solar-powered LED glow at hand you have a lightweight, waterproof and reliable light source for camping, boating, night hiking or any unforeseen circumstances Mother Nature delivers.

Versatile Luci has three convenient settings including a high visibility emergency flashing setting. Luci Outdoor is the same great light as Luci Original, but packaged for the outdoor enthusiast.

Designed for backpacking, rock climbing, camping, barbecuing, hiking, biking, fishing and residential use. Powered by the sun's free energy, Luci lights are safer, cleaner and brighter than candles and kerosene and longer lasting than batteries. The solar lantern fits easily into any drawer, pocket, glovebox or



- * Safe and Rechargeable
- * Works In Any Weather
- * Lightweight and Collapsible
- * Weight: 4 oz

Charging Features

- * Rechargeable lithium polymer battery pack
- * 300-500 cycle lifetime Rating (2+ years daily use)
- * Over charge/discharge protection
- * Over current and short circuit protection
- * Lasts up to 12 hours on bright setting (charges in 8 hours under full sunlight)
- * Retains 95% charge/month when in storage
- * Charges in both direct sunlight and artificial light

Technical Features

- * Solar panel dimensions: 75mm x 75mm
- * Open circuit voltage (Voc): 6.0V
- * Optimum operating current (Imp): 150mA
- * Charging power: 0.6W
- * LED current (max): 200mA
- * Battery: lithium-ion polymer, 3.7V, 1000mAh* Storage temperature: -20°C to 52°C
- * Operating temperature: -10°C to 50°C
- * Maximum short term, non-operating temperature exposure: 60°C
- * Maximum inflation pressure: 5.0kPa (0.75psi)
- * Material: Phthalate free, waterproof PVC enclosure

One Year Manufacturers Warranty!