

# NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers (250 USD)



Location **Utah**  
<https://www.genclassifieds.com/x-565614-z>

I have a pair of 12" eighteen sound high performance transducers for sale. These retail for around \$200 per speaker. Asking \$250 for the pair. Call or text if interested. Click "more ads by seller" to see my other listings.

## KeyFeatures:

- 96 dB SPL 1W / 1m average sensitivity
- 75 mm (3 in) Interleaved Sandwich Voice coil (ISV)
- 500 W AES power handling
- Double Silicon Spider (DSS) for improved control and linearity
- Improved heat dissipation via unique basket design
- Weather protected cone and plates for outdoor usage Ideal for compact reflex subwoofer

## Description:


The 12LW800 is a low frequency loudspeaker which sets a new industry standard in 12" (300mm) Å high performance transducers, achieving a remarkable 42Hz downwards extension with 96dB average sensitivity, handling peak power levels of 4000W with remarkably low distortion and excellent transient response.

The 12LW800 is intended as the low bass or sub-woofer component, either in highly compact reflex, or in a large horn loudspeaker configuration. It has a clear, low frequency response, and at high power levels, is part of a compact, high power, reflex system. The reflex configuration can be used in a compact, high power, 40 - 70 Hz band, or ideally, as a portable, high power, such as a stage monitor, or a bass monitor, or a stage monitor.

The high excursion capabilities of the double action roll surround and suspension system, in conjunction with the Eighteen Sound Double Silicon Spider (DSS), has enabled the 12LW800 to achieve very high levels of linear travel for a 12" unit.


The carbon fibre reinforced curvilinear ribbed cone, with its custom design surround, assures smooth response and exceptional strength with maximum reliability under high mechanical stress.

The 75mm Å state-of-the-art voice coil is similar to that fitted to our 8LW1400 top-of-the-range model. It employs our Interleaved Sandwich Voice coil (ISV) in which a high strength fiberglass former carries




**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>




**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>




**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>



**NEW Eighteen Sound 12 Weather Resistant Low Frequency Loudspeakers**

<https://www.genclassifieds.com/x-565614-z>

---

windings on both the outer and inner surfaces to achieve a mass balanced coil and providing a uniform motive drive. This, in conjunction with the use of unique high temperature resin adhesives, results in an extremely linear motor assembly with reduced tendency to break-up under high drive conditions.

Excellent heat dissipation is achieved by the incorporation of air channels between the basket and top plate.

Maximum flux concentration and force factor in the gap is assured by the unique shape and design of the face and back plates, these having been researched and designed using our in-house Magnetic Flux FEA CAD resource.

With the increasing use of high power audio systems at outdoor events or in a marine environment, the ability to perform properly under inclement weather conditions is another part of the Eighteen Sound philosophy. This is achieved by means of an exclusive cone treatment improving pulp strength and giving water repellent properties to the

cone. In addition, special treatment of both the face and back plates results in a product which is far more resistant to the corrosive effects of salts and oxidation than any other treatment in use.

#### General Specifications:

Nominal Diameter 300 mm (12 in)

Rated Impedance 8 Ohm

AES Power 500 W

Program Power 800 W

Peak Power 4000 W

Sensitivity 96 dB

Frequency Range 46 Å 4200 Hz

Power Compression @-10dB 0,9 dB

Power Compression @-3dB 2,6 dB

Power Compression @Full Power 4 dB

Max Recomm. Frequency 1300 Hz

Recomm. Enclosure Volume 40 Å 100 lt. (1,41 Å 3,53 cuft)

Max Peak To Peak Excursion 34 mm (1,34 in)

Voice Coil Diameter 75 mm (2,95 in)

Voice Coil Winding Material copper

Suspension Single roll, rubber

Cone Curvilinear ribbed, Paper

Thiele Small Parameters

Fs 52 Hz

Re 5,6 Ohm

Sd 0,0531 sq.mt. (82,31 sq.in.)

Qms 7,6

---

Qes 0,3  
Qts 0,29  
Vas 48 lt. (1,70 cuft)  
Mms 76,5 gr. (0,17 lb)  
BL 21,3 Tm  
Linear Mathematical Xmax  $\hat{A}\pm 6,5$  mm ( $\hat{A}\pm 0,26$  in)  
Le (1kHz) 1,72 mH  
Ref. Efficiency 1W@1m (half space) 95,5 dB  
Mounting information

Overall diameter 315 mm (12,4 in)  
N. of mounting holes and bolt 8  
Mounting holes diameter 7,15 mm (0,28 in)  
Bolt circle diameter 296 - 300 mm (11,65 - 11,8 in)  
Front mount baffle cutout  $\hat{A}$ , 282 mm (11,1 in)  
Rear mount baffle cutout  $\hat{A}$ , 282 mm  
Total depth 151 mm (5,94 in)  
Flange and gasket thickness 20 mm (0,79 in)  
Flange and gasket thickness 20 mm (0,79 in)  
Net weight 8,1 kg (17,88 lb)  
Shipping weight 8,9 kg (19,65 lb)  
CardBoard Packaging dimensions 332 x 332 x 184 mm (13,07 x 13,07 x 7,24 in)